









cloud

## OUTDOOR COMPACT RFID DEVICE



RFID technology and multi-hardware platform. With the multi-form factor technology, mullion-type, gangbox-type, and gangbox keypad-type are all supported which Provides perfect installation in various environments. XPass 2 also supports dual-frequency (125kHz / 13.56MHz) RFID technology and can read the mobile cards using NFC and BEID, the latest mobile communication technologies. Packed in a rugged IP65/IP67 rated dust & waterproof performance as well as IK08 rated Vandal-proof structure, suitable for tough environmental and outdoor installation.

## Features

-  Mobile card (NFC and BLE)
-  Industry standard communication via OSDP
-  Multi-type hardware structure
-  Enhanced security with the Secure Element
-  IP67 - Water and Dust Resistant
-  IK08 - Vandal Resistant
-  Multi-card Reading
-  Power over Ethernet

## Specification

T25kHz card compatibility	EM
T3.56MHz card compatibility	MIFARE, MIFARE Plus, DESFire/EV1, FelICA
CPU	1.0GHz
Memory	4GB Flash + 64MB SDRAM
Max. Users	200,000
Max. Text Logs	1,000,000
Mobile card	NFC, BLE
IP rating	IP65, IP67
IK rating	IK08
Installation type	Mullion: XP2-MDPB Gangbox: XP2-GDPB, XP2-GKDPB
Keypad	Not Supported : XP2-MDPB, XP2-GDPB Supported (3x4): XP2-GKDPB
Ethernet	Supported (10/100 Mbps, auto MDI/MDI-X)
RS-485	1ch Master or Slave
Wiegand	1ch In or Out
TTL	2ch Input
Relay	1 Relay
PoE	Supported (IEEE 802.3af compliant)
Sound	Multi-tone buzzer
Operating Temperature	-35 °C ~ 65 °C
Operating Humidity	0% ~ 95%, non-condensing
Power	DC 12V or DC 24V
Dimensions (WxHxD, mm)	48 x 145 x 27: XP2-MDPB 80 x 130 x 25: XP2-GDPB, XP2-GKDPB
Certificates	CE, FCC, KC, RoHS, REACH, WEEE, SIG

## System Configurations

