


cloud



**CWS7000**  
2d barcode scanner

## Features

### Excellent Scanning Performance

Extended reading distances and improved capability of reading small, condensed, curved, poorly printed, and reflective bar codes

### REALIABILITY

Its durable housing guarantees optimal protection and backed by a 2 year warranty.

### MARKETS AND APPLICATION

Point of sale/retail, product traceability, track & trace healthcare, inventory management, ticket / voucher management, general office automation.

### Cordless Freedom

Wireless frees workers from cords, allowing cashiers to easily scan items inside and outside of the cash wrap. The cradle is working as charging and data receiving function.

### Real Time and Batch Mode Support

Ensures compatibility with your current applications and allows users to capture data, regardless of whether they are on or offline.

## Application



retail



manufacturing



healthcare

## CWS7000 Technical Specification

|             |                       |  |  |
|-------------|-----------------------|--|--|
| Performance | Image Sensor          | 640*480  |  |
|             | Decode Capacities     | 1D   | EAN-8、EAN-13、EAN-13 2 add-on、EAN-13 5 add-on、ISBN、UPC-A、UPC-E Code 39、Code 39 FullASCII、Code 93、Code 128、Codabar、Industrial 2 of 5、Interleaved 2 of 5 Matrix 2 of 5、GS1-128、GS1 DataBar (RSS14) (Stacked)、GS1 DataBar Limited、Standard 25 GS1 DataBar Expanded |
|             |                       | 2D   | PDF417 MicroPDF417、MicroQR、DataMatrix QR Code  |
|             | Scan Range            | Typical Performance  |  |
|             |                       | UPC-13mil  | : 3-29cm   |
|             |                       | Code39 20mil   | : 7-50cm   |
|             | Scan Rate             | 60FPS  |  |
|             | Countries Keyboards   | English, German, French, Italian, Spanish, Belgian (French) ,Portuguese,Japanese |  |
|             | Wireless Range        | 80 meters open space   |  |
|             | Min Symbol Contrast   | 25%  |  |
|             | Sealing Level         | IP42   |  |
|             |                       | 1600mA   |  |
| Physical    | Interface             | BT-HID,BT-BLE,BT-SPP, USB-HID  |  |
|             | Operating Temperature | 0-40°C   |  |
|             | Storage Temperature   | -20-60°C   |  |
|             | Dimension             | 113mm* 82.5mm*163.7mm  |  |